



THE ECONOMIC SOLUTION FOR PRINTING.

PRODUCT

FOREX[®]print sheet material is specially designed to meet the requirements in the field of printing. The extremely lightweight sheet is outstanding due to its brilliant white, smooth, even surface which forms the basis for a perfect printing result, particularly for direct digital printing.

PROTECTIVE FILM

- PE film on one side as standard
- Protective PE film on both sides on request

APPLICATIONS

- Digitally and screen printed panels
- Short- and mid-term advertising campaigns
- Signage
- Ideal lamination substrate
- Flat applications

Due to its surface structure, FOREX[®]print attains optimum ink adhesion for printing and is extremely colour-fast. The sheet material is suitable for flat applications in such fields as sign-making and advertising for short-term and medium-term use. FOREX[®]print enables economic solutions in the field of printing applications.

FOREX[®]print ¹ AT A GLANCE

- Brilliant white, smooth, even surface for good printability, especially for direct digital printing
- Optimum ink adhesion and colour fastness
- Good dimensional accuracy of the sheets
- Suitable for flat applications
- Practicable for shorter to medium-term applications for interior and exterior use
- °Ready to use¹ can be printed on directly without any pre-treatment required
- Provided with protective film
- Fire behavior according to:
 - > DIN EN 13501-1: C - s3 - d0 (2 - 10 mm)
 - > BS 476-7, Class 1 (10 mm)

COLOUR



PRODUCT RANGE

Thickness mm	2	3	4	5	6	8	10
Standard formats (Wx L)							
1220 x 2440 mm	■	■		■			■
1220 x 3050 mm		■		■			■
1560 x 3050 mm	■	■	■	■			■
2030 x 3050 mm	■	■	■	■	■	■	■

The given measurements are standard dimensions, ex works. Special sheet sizes upon request, sheets cut to size can be obtained from your distributor.

